

# SURE SEAL® 24/7 STONE IMPREGNATOR

## Water Based Sealer



Sure Seal® Stone Sealer provides unparalleled protection against water and oil-based stains, and alkalis to maintain the natural look and beauty of the stone. It is invisible upon application, and will not change the appearance of the treated surface. There is no residue, "whiting", puddling, discoloration, etching, or yellowing of the treated surface and Stone Sealer allows the treated area to breathe.

### Benefits & Characteristics

- Non-toxic, Water based, and V.O.C. free
- Non-flammable
- Environmentally friendly
- Odorless and invisible impregnator
- Non-yellowing and U.V. light resistant
- Resists oil, and water based stains
- User friendly and easy to apply
- No silicones
- Inhibits Efflorescence and Freeze Thaw
- Preserves Natural Look
- Deep Penetrating Protection
- Interior and Exterior Use

### Directions for Use

**Uses:** This product is a superior water-based, silicone free impregnator to help prevent oil and water-based stains, moss and efflorescence on all types of masonry surfaces, including marble, granite, slate, sandstone, limestone, architectural concrete, brick, stone, stucco and exposed aggregate, etc. It also helps prevent chewing gum from adhering to the surface of a substrate.

As with all Sure Seal® products, it is invisible upon application and will not puddle, whiten, peel or flake off the treated surface.

**Directions for Application:** Always ensure that the surface is clean and free from debris and previous sealants and waxes Any existing stains must be removed prior to sealant application. Apply by brush, roller or garden-type sprayer. One good coat is usually sufficient. However, on very porous surfaces or heavy walkway areas, two coats are recommended, Allow five hours between applications of each coat. Normal drying time on marble or granite is approximately 20 minutes. However, buff before completely dry At least eight hours drying time is recommended before traffic should be allowed on the treated area. For optimal protection, allow to cure for 24 hours.

**Maintenance:** To clean exterior treated areas, use a garden hose with a pressure nozzle or pressure washer with a maximum pressure of 1000 PSI. For interior applications simply mop or wipe with a soft cloth or sponge and a mild liquid cleaner or water. Do not use harsh cleaning agents such as abrasive powders, ammonia, acids, bleach, solvents or abrasive scrubbing pads.

**Note:** Consult the Sure Seal® Stone Sealer Material Safety Data Sheet for details regarding Hazardous Properties and Personal Protective Equipment requirements.

**Expected Wear:** Sure Seal® will last for many years with proper maintenance on all treated surfaces: however, heavy walkway areas should be tested yearly and product reapplied if necessary

**Warranty:** Satisfaction guaranteed, if not completely satisfied with product performance, when used as directed, contact Sure Seal for product replacement or refund of purchase price upon return of unused portion. Replacement cost for labor and installation materials are excluded. Any variance from the terms, misuse or misapplication of the product shall void and nullify this warranty.

**Appearance/Odor:** A yellow solution with a mild odor

**Packaging:** Product is supplied in 5 litre containers (5 x 4 litres to a carton) and 20 litre drums.

**Coverage:** One litre will cover approximately 10-15 sq. metres, depending upon the porosity of the substrate. At least eight hours drying time is recommended before traffic should be allowed on the treated area. After sealant has dried for optimal protection, allow to cure for 24 hours.

**Storage/Shelf Life:** Keep sealed in original containers and store in a cool dry place. When properly stored, shelf life is six months from date of opening the container. Do not allow to freeze.

**Transport Information:** Proper Shipping Name: None Allocated Not regulated (Not classified as a Dangerous Good, according to the Australian code for the Transport of Dangerous Goods by Road and Rail (6th Edition))

**Note:** Consult the Sure Seal® Stone Sealer Material Safety Data Sheet for details regarding Hazardous Properties and Personal Protective Equipment requirements.

