

### PENETRATING SEALER

#### **DESCRIPTION:**

AQUA MIX PENETRATING SEALER is an economical, no-sheen, natural-look, water-based, penetrating sealer designed to resist stains. May also be used as a pre-grouting sealer. Allows moisture vapor transmission. It is also a good grout sealer.

#### **USES:**

Recommended for use on:

- All natural stone (such as granite, limestone, marble, slate, and travertine.), porcelain, quarry, saltillo, terra cotta, cement pavers, masonry surfaces, and other porous tile and grout where a natural look is desired.
- Effective for interior and exterior applications.

#### **COVERAGE:**

Approximately 300 to 1,000 sq. ft. (30 m<sup>2</sup> to 95 m<sup>2</sup>) per coat per gallon (3.785 L), depending on type of stone or tile, porosity and texture of surface, temperature, humidity, and method of application.

#### **EXPECTED WEAR:**

- Will vary depending on hardness and texture of surface, type of area, surface wear, frequency, and type of maintenance products used.
- The expected wear is **up to 5 years**.
- Weather conditions, harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners will affect wear.

#### **TEST A SMALL AREA:**

According to application instructions with a 24-hour cure time to determine desired results. Test for stain repellency using likely contaminants.

#### **APPLICATION:**

- 1.) **Read entire label before using.**
- 2.) For new installations, sealer can be applied as soon as 48 hours after grouting.
- 3.) Surface must be clean, dry, and free of existing sealers or coatings.
- 4.) Apply using a sponge, brush, paint pad, cotton towel, or sprayer.  
**NOTE: Be sure any sealer that does not penetrate surface is polished dry off surface within 5 minutes of application using absorbent paper or cotton towels.**
- 5.) If 2 or more coats are applied, allow a minimum of 30 minutes drying time between coats.
- 6.) 2 hours after final coat conduct a test to determine if surface is completely sealed by applying water droplets to the surface. If water is absorbed, apply an additional coat. Wait 2 hours and repeat the test.
- 7.) Ready for surface traffic in 2 hours after final coat. Keep area dry for at least 12 hours. Achieves a full cure in 24 hours.
- 8.) Clean applicator tools with water after each use.

#### **FOR PRE-GROUTING APPLICATION:**

Apply over clean stone or tile a minimum of 2 hours prior to grouting - follow application procedures above.

#### **MAINTENANCE:**

- Aqua Mix Concentrated Stone & Tile Cleaner,
- Cleaning Wipes with Sealer's Choice™ or
- Tile Plus More Antibacterial Cleaner are recommended for routine cleaning.

#### **TECHNICAL ASSISTANCE:**

Call 877-278-2311, Monday through Friday, 6:00 a.m. to 4:30 p.m. or Saturday, 7:00 a.m. to 12:00 p.m. Pacific Time.

#### **LIMITATIONS:**

- Do not allow product to come in contact with any non-recommended surface.
- If product is allowed to dry on surface, a white film may form.
- If this occurs, scrub surface with water and a white nylon pad.
- Sealer will not prevent surface wear or etching from acids or caustic chemicals.
- Note: Aqua Mix Ultra-Solv™ or Sealer's Choice™ Gold are recommended in place of Penetrating Sealer in food preparation areas or where maximum stain protection is required.

#### **HANDLING AND STORAGE:**

- Close container tightly after each use.
- Store in original container only.
- Store and use between temperatures of 40 °F and 90 °F (4 °C and 32 °C).
- Unused, stored product is freeze-thaw stable.

#### **CAUTION:**

- **KEEP OUT OF REACH OF CHILDREN.**
- Contains siliconates.
- Do not take internally.
- Rubber gloves and eye protection should be worn during application.
- **IF INGESTED:** Do not induce vomiting. Drink 1 to 2 glasses of water. Seek immediate medical attention.
- **EYE CONTACT:** Flush thoroughly with water. Seek immediate medical attention.
- **SKIN CONTACT:** Flush with water.

#### **WARRANTY:**

**SATISFACTION GUARANTEED.** If not completely satisfied with this product's performance, **when used as directed**, contact Aqua Mix for exclusive remedy of either refund of purchase price or replacement of product upon return of unused portion with proof of purchase within one year of purchase. Determining suitability of product for any intended purpose shall be solely the responsibility of the user. **THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE, WHICH EXTEND BEYOND THE DESCRIPTION ON THIS LABEL. IN NO EVENT SHALL AQUA MIX BE LIABLE TO THE CUSTOMER OR ANYONE ELSE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, HOWEVER OCCASIONED. ALWAYS TEST FIRST.**