

ULTRA-SOLV™

DESCRIPTION:

AQUA MIX ULTRA-SOLV™ is a premium, no-sheen, natural-look, solvent-based, penetrating sealer formulated to provide maximum stain protection, especially in food preparation and serving areas. May also be used as a pre-grouting sealer. Allows moisture vapor transmission. It is also an excellent grout sealer.

USES:

Recommended for use on:

- All natural stone (such as marble, granite, slate, travertine and limestone), porcelain, quarry, saltillo, terra cotta, cement pavers, masonry surfaces, and other porous tile and grout where a natural look is desired.
- Equally effective for interior and exterior applications.

COVERAGE:

Approximately 400 to 1,500 sq. ft. (37 m² to 139 m²) per coat per gallon (3.785 L), depending on type of stone, porosity and texture of surface, temperature, humidity, and method of application.

EXPECTED WEAR:

- Will vary depending on hardness and texture of surface, type of area, surface wear, frequency, and type of maintenance products used.
- The expected wear is **up to 15 years**.
- Weather conditions, harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners will affect wear.

TEST A SMALL AREA:

According to application instructions with a 24-hour cure time to determine desired results. Test for stain repellency using likely contaminants.

APPLICATION:

- 1.) **Read entire label before using.**
- 2.) For new installations, sealer can be applied as soon as 48 hours after grouting.
- 3.) Surface must be clean, dry, and free of existing sealers or coatings.
- 4.) Apply using a sponge, brush, paint pad, cotton towel, or sprayer. **NOTE: Be sure any sealer that does not penetrate surface is polished dry off surface within 5 minutes of application using absorbent paper or cotton towels.**
- 5.) If 2 or more coats are applied, allow a minimum of 30 minutes drying time between coats.
- 6.) After 2 hours conduct a test to determine if surface is completely sealed by applying water droplets to the surface. If water is absorbed, apply an additional coat. Wait 2 hours and repeat the test.
- 7.) Ready for surface traffic in 2 hours after final coat. Keep area dry for 12 hours. Achieves a full cure in 24 hours.
- 8.) Clean applicator tools with mineral spirits after each use.

PRE-GROUTING APPLICATION:

Apply over clean stone or tile a minimum of 2 hours prior to grouting - follow application procedures above.

MAINTENANCE:

- Aqua Mix Cleaning Wipes with Sealer's Choice™
- Concentrated Stone and Tile Cleaner, or
- Tile Plus More Antibacterial Cleaner are recommended for routine cleaning.

TECHNICAL ASSISTANCE:

Call 877-278-2311, Monday through Friday, 6:00 a.m. to 4:30 p.m. or Saturday, 7:00 a.m. to 12:00 p.m. Pacific Time.

LIMITATIONS:

- Do not allow sealer to come in contact with any non-recommended surface.
- May slightly lighten or darken some stone surfaces.
- Sealer will not prevent surface wear or etching from acids or caustic chemicals.

HANDLING AND STORAGE:

- Close container tightly after each use.
- Store in original container only.
- Store and use between temperatures of 40 °F and 90 °F (4 °C and 32 °C).
- Unused, stored product is freeze-thaw stable.
- Dispose of residue or any unused leftover product in accordance with applicable federal, state, and local requirements.

CAUTION:

- **KEEP OUT OF REACH OF CHILDREN.**
- **DANGER:** Combustible. Contains petroleum distillates
- Use in well-ventilated areas.
- Avoid prolonged skin contact.
- **Wear NIOSH approved respirator, solvent-resistant gloves, safety goggles, and protective clothing.**
- **IF INGESTED:** Do not induce vomiting. Drink 1 to 2 glasses of water. Call physician immediately.
- **EYE CONTACT:** Flush with water. If irritation persists, seek medical attention.
- **SKIN CONTACT:** Wash immediately with soap and water. If irritation persists, seek medical attention.
- **INHALATION:** Relocate to fresh air. If symptoms persist, seek medical attention.

WARRANTY:

SATISFACTION GUARANTEED. If not completely satisfied with this product's performance, **when used as directed**, contact Aqua Mix for exclusive remedy of either refund of purchase price or replacement of product upon return of unused portion with proof of purchase within one year of purchase. Determining suitability of product for any intended purpose shall be solely the responsibility of the user. **THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE, WHICH EXTEND BEYOND THE DESCRIPTION ON THIS LABEL. IN NO EVENT SHALL AQUA MIX BE LIABLE TO THE CUSTOMER OR ANYONE ELSE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES, HOWEVER OCCASIONED. ALWAYS TEST FIRST.**